

William Heung P.E.

Engineering Support Branch
Waste Permitting, Compliance, and Mitigation Division
CalRecycle

How to Get from Here to There



Before

After



ICS Structure

INCIDENT COMMAND

OPERATIONS

BRANCH

DIVISION

TASK FORCE

Task Force Details

- Typically Composed of the Following Crew:
 - 1 Task Force Leader/Debris
 Monitor
 - 1 Foreman
 - 1 to 2 Operators
 - 3 to 4 Laborers
 - 1 Water Truck Tenders




Equipment - Excavator





Equipment - Excavator





Equipment – Skid Steer



Equipment – Skid Steer



Equipment – Skid Steer



Equipment – Water Trucks



Equipment – Water Trucks




Equipment – Low Boy

Valley Fire – Approximately 50 crews completing 1 site every 1.5 to 2 days = 25 to 33 trips per day!

















Equipment – Tractor / Front Loader



Equipment – Disposal Trucks





Equipment – Disposal Trucks



Equipment – Disposal Trucks



Specialized Equipment - Roads






Specialized Equipment - Bridges




Specialized Equipment - Misc





Specialized Equipment - Misc



Debris Removal Timeline

- <u>Typical</u> Debris Removal Timeline:
 - Site Assessment
 - Hazardous Materials
 - Asbestos Survey and Removal
 - Vehicles / Chimneys
 - Metals
 - Ash/Debris
 - Concrete











- Identify property lot lines on each property.
- Identify septic tank and leach field locations on each property.
- Identify water wells, springs, other water sources and water storage tanks on properties not serviced by the local water agency.
- Measure and record foundation and other hardscape footprints.
- Measure and record ash footprints.
- Identify other property-specific hazards (i.e. swimming pools, large vehicles, hazard trees).
- Conduct radiation sweep.
- Identify, sample, analyze, and remove asbestos containing materials.

Debris Removal – Hazardous Materials

- Pressurized tanks
- Unexploded Ordnance
- Misc. Solvents
- E Waste
- Household Hazardous Waste



Debris Removal - Asbestos

- Hauled to Lined Class III Landfill, permitted to accept asbestos
 - Insulation
 - Pipes
 - Tiles
 - Chimney mortar





Debris Removal - Vehicles

Recycled as metal after Insurance and DMV is contacted





Debris Removal - Chimneys

Disposed as ash/debris unless containing asbestos (new requirement)



Debris Removal - Metal

• Recycled as scrap. Money gained goes to defray cost of project





Debris Removal - Metal

- Garage doors
- Appliances
- Structural metal (I-Beams)
- Electrical equipment
- Trailers



Debris Removal – Ash/Debris

• Disposed as waste. "Burrito" wrapped in plastic



Debris Removal – Ash/Debris



Debris Removal - Concrete

Recycled if possible, if not goes out as waste




Debris Removal - Concrete




"Why do you have to remove the concrete foundation?"

- What is Concrete?
- What is Reinforced Concrete?
- Other terms used: Cement, Pavement, Asphalt
- Concrete is the second most consumed material in the world after water
- Almost 3 tons of concrete produced each year for every human on the planet

CEMENT: Fine mineral powder (mostly lime and silica). Mixed with water, produces a paste which hardens and binds.




CONCRETE: Sand and gravel (aggregate) bounded with cement




BENEFITS OF CONCRETE: Inert, High Specific Heat, Durable, Cheap


REINFORCED CONCRETE: Concrete with metal



BENEFITS OF REINFORCED CONCRETE: Durability of Concrete with tensile strength of steel



- Properties of Concrete
 - Inert to fire, durable, cheap
 - Conducts heat <u>VERY</u> slowly
 - Concrete exposed to heat for 1 hour:
 - Surface Temp = 600 °C
 - 1 inch below Surface = 300 °C
- Even at partial strength, concrete is very strong



- At 300 °C, Concrete is at 85% to 60% strength
- At 550 °C, Concrete is at 45% to 30% strength
- At 900 °C, aggregates pulverize and cement paste fragments, leaving gaps in the slab
- Average Wildfire temp: 800 °C, can reach up to 1200 °C
- Embers of homes keeps elevated temperatures for days
- Heat reduces bonding strength of rebar to concrete

- Nonstructural Reasons for Removal
 - Contamination around slabs
 - Limitations of future home design
 - Utility connections (reconnect)
 - Earthquake anchor bolts compromised
 - Cost for homeowners

- Rebuilding on Damaged Foundation
 - Varies County by County
 - Core samples can be taken for strength testing
 - Compressive versus Sheer



- Rare instances concrete is left
 - Driveways
 - Well/pump houses





Debris Removal - Soil

 Soil – Used for ADC if possible (pending approval by Water Board, depending on soil characteristics), disposed as waste otherwise



Debris Removal – 3 Year Old Standard



Items We Don't Remove

- Trees (unless hazard to the crew)
- Areas away from living areas
- Partially burned/impacted structures
- Fences
- Swimming pools
- Retaining walls
- Septic Tanks
- Underground utilities
- Minimum debris quantity (cost driven)

Soil Confirmation Sampling



Is the Ash Hazardous or Toxic?

The ash is an immediate threat to public health and safety (source: Cal/EPA)

- Residual structural ash contains concentrated amounts of "heavy metals", such as arsenic, beryllium, cadmium, cobalt, copper, lead, mercury, nickel, thallium, vanadium, and zinc
- Asbestos is also present in older home sites (pre 1985 ish)
- Asbestos and Lead <u>very prevalent in older communities pre-1978</u>

Preliminary Risk Analysis indicated health related issues with the ash from

heavy metals



Soil Confirmation Sampling

- Samples locations and frequency are determined based on removal area and structures
- Collect samples and send to lab for analysis
- Compare soil results to cleanup goals
- If results exceed cleanup goals, another layer of soil will be removed for disposal and the site re-sampled
- If results are less than cleanup goals, debris removal is considered complete



Soil Confirmation Sampling

| Clayton Cleanup Goals | East Div | West Div |
|-----------------------|----------|----------|
| Antimony | 30 | 30 |
| Arsenic | 11.376 | 11.4 |
| Barium | 5200 | 5200 |
| Beryllium | 15 | 15 |
| Cadmium | 1.7 | 1.7 |
| Chromium | 36000 | 36000 |
| Cobalt | 24.1 | 24.1 |
| Copper | 3000 | 3000 |
| Lead | 80 | 125.7 |
| Mercury | 5.1 | 5.1 |
| Molybdenum | 380 | 380 |
| Nickel | 490 | 490 |
| Selenium | 380 | 380 |
| Silver | 380 | 380 |
| Thallium | 0.78 | 5 |
| Vanadium | 390 | 390 |
| Zinc | 23000 | 23000 |

| CONFIRMATION SAMPLING | | |
|---------------------------------|-------------------------------|------------------------------------|
| UNIFIED COMMAND APPROVAL | FORM | |
| SITE ADDRESS: | | |
| Sample Identification: | Number of Samples: | <u> </u> |
| Date Sample Collected: | Laboratory: BC Labo | ratories, Inc. |
| Cleanup Goals: See Metals Clean | up Goals for the Clayton Fire | e Site in Lake County, California. |
| Date Approved: | | |
| Observations: | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |